

Series 320

CEJN ORIGINAL STANDARD, EUROSTANDARD 7.6 (7.4)


GLOBAL

- Vented safety function
- Extremely high flow capacity
- Compact design

eSafe Series 320 coupling is an easy-to-handle high performing coupling with a long service life. eSafe is a one hand operated safety coupling that vents before disconnection eliminating the risk of hose whip. Male threads on the couplings and nipples feature pre-applied thread sealant. The couplings have a smaller outside dimension than comparable designs. Full automatic operation ensures easy handling. eSafe complies with ISO Standard 4414 and EN 983.

Serie 320 is also available in standard, Soft-Line and Multi-Link versions.

TECHNICAL DATA



7.6 mm (5/16") 2250 l/min (79.4 CFM) 16 bar (230 PSI) 140 bar (2030 PSI) 86 N


-20°C - +100°C (-4°F - +212°F) Zinc-plated steel/brass

Hardened zinc-plated steel
Parker Rectus 25/26, Parker Tema 1600/1625, Prevost ESC07/
ERC07/ESI07/ISC08, Oetiker SC C, Hansen Auto-Flo 24

Flow capacity is measured at 6 bar (87 PSI) inlet pressure, and pressure drop at 0.5 bar (7 PSI).



AIR FLOW



Flow, I/min. (C	FM
-----------------	----

		Part No.	Connection			Part No.	Connection
ESAFE VENTED SAFETY COUPLING	HOSE CONNECTION	103202002	6.3 mm (1/4")	NIPPLES	HOSE CONNECTION	103205001	5.0 mm (3/16")
		103202003	6.3 mm (5/16")			103205002	6.3 mm (1/4")
		103202004	10 mm (3/8")			103205003	8.0 mm (5/16")
		103202005	13 mm (1/2")			103205004	10.0 mm (3/8")
					MALE THREAD	103205151	R 1/8"
	MALE THREAD	103202152	R 1/4"			103205152	R 1/4"
	CONNECTION	103202154	R 3/8"			103205154	R 3/8"
		103202155	R 1/2"			103205263	G 1/4"
	1 B 1 B	103202452	NPT 1/4"		_	103205264	G 3/8"
		103202454	NPT 3/8"			103205265	G 1/2"
		103202455	NPT 1/2"			103205451	1/8" NPT
		103202433	141 1 1/2			103205452	1/4" NPT
		40000000	C 4 /4"			103205454	3/8" NPT
	FEMALE THREAD CONNECTION	103202202	G 1/4"			103205455	1/2" NPT
		103202204	G 3/8"		FEMALE THREAD	103205201	G 1/8"
		103202205	G 1/2"			103205202	G 1/4"
		103202402	NPT 1/4"			103205204	G 3/8"
		103202404	NPT 3/8"			103205401	1/8" NPT
		103202405	NPT 1/2"			103205402	1/4" NPT
						103205404	3/8" NPT
	STREAM-LINE CONNECTION	103202060	6.5 x 10 mm			103205405	NPT 1/2"
		103202063	9.5 x 13.5 mm		STREAM-LINE	103205058	5x8 mm
		103202066	11 x 16 mm		CONNECTION	103205060	6.5x10 mm
						103205062	8x12 mm
						103205063	9.5x13.5 mm
						103205066	11 x 16 mm
	SOFT-LINE	103202080	6.5 x 10 mm				
		103202082	8 x 12 mm				

Thread connections are listed according to ISO Standards. All measurements are in mm. Check with an authorized CEJN distributor for availability and prices. Please visit our web site, www.cejn.com, for general maintenance tips.