

Soudal Flexifoam

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier:

Product name : Soudal Flexifoam
 Registration number REACH : Not applicable (mixture)
 Product type REACH : Mixture

1.2 Relevant identified uses of the substance or mixture and uses advised against:

1.2.1 Relevant identified uses

polyurethane

1.2.2 Uses advised against

No uses advised against known

1.3 Details of the supplier of the safety data sheet:

Supplier of the safety data sheet

Soudal N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 +32 14 42 65 14
 msds@soudal.com

Manufacturer of the product

Soudal N.V.
 Everdongenlaan 18-20
 B-2300 Turnhout
 ☎ +32 14 42 42 31
 +32 14 42 65 14
 msds@soudal.com

1.4 Emergency telephone number:

24h/24h (Telephone advice: English, French, German, Dutch):
 +32 14 58 45 45 (BIG)

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture:

2.1.1 Classification according to Regulation EC No 1272/2008

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

Class	Category	Hazard statements
Aerosol	category 1	H222: Extremely flammable aerosol.
Aerosol	category 1	H229: Pressurised container: May burst if heated.
Carc.	category 2	H351: Suspected of causing cancer.
Acute Tox.	category 4	H332: Harmful if inhaled.
STOT RE	category 2	H373: May cause damage to organs through prolonged or repeated exposure if inhaled.
Eye Irrit.	category 2	H319: Causes serious eye irritation.
STOT SE	category 3	H335: May cause respiratory irritation.
Skin Irrit.	category 2	H315: Causes skin irritation.
Resp. Sens.	category 1	H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Sens.	category 1	H317: May cause an allergic skin reaction.

2.1.2 Classification according to Directive 67/548/EEC-1999/45/EC

Classified as dangerous in accordance with the criteria of Directives 67/548/EEC and 1999/45/EC

Carc. Cat. 3; R40 - Limited evidence of a carcinogenic effect

F+; R12 - Extremely flammable.

Xn; R20 - 48/20 - Harmful by inhalation. Harmful: danger of serious damage to health by prolonged exposure through inhalation.

Xi; R36/37/38 - Irritating to eyes, respiratory system and skin.

R42/43 - May cause sensitisation by inhalation and skin contact.

2.2 Label elements:

Labelling according to Regulation EC No 1272/2008 (CLP)

Soudal Flexifoam



Contains: polymethylene polyphenyl isocyanate.

Signal word

Danger

H-statements

- | | |
|------|-------------------------------------------------------------------------------|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: May burst if heated. |
| H351 | Suspected of causing cancer. |
| H332 | Harmful if inhaled. |
| H373 | May cause damage to organs through prolonged or repeated exposure if inhaled. |
| H319 | Causes serious eye irritation. |
| H335 | May cause respiratory irritation. |
| H315 | Causes skin irritation. |
| H334 | May cause allergy or asthma symptoms or breathing difficulties if inhaled. |
| H317 | May cause an allergic skin reaction. |

P-statements

- | | |
|-------------|----------------------------------------------------------------------------------------------------|
| P101 | If medical advice is needed, have product container or label at hand. |
| P102 | Keep out of reach of children. |
| P210 | Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. |
| P211 | Do not spray on an open flame or other ignition source. |
| P251 | Do not pierce or burn, even after use. |
| P280 | Wear protective gloves, protective clothing and eye protection/face protection. |
| P362 + P364 | Take off contaminated clothing and wash it before reuse. |
| P410 + P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122°F. |
| P501 | Dispose of contents/container in accordance with local/regional/national/international regulation. |

Supplemental information

- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
- Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
- This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

Labelling according to Directive 67/548/EEC-1999/45/EC (DSD/DPD)

Labels



Extremely flammable



Harmful

Contains: polymethylene polyphenyl isocyanate.

R-phrases

- | | |
|----------|--------------------------------------------------------------------------------------|
| 20 | Harmful by inhalation |
| 36/37/38 | Irritating to eyes, respiratory system and skin |
| 40 | Limited evidence of a carcinogenic effect |
| 42/43 | May cause sensitisation by inhalation and skin contact |
| 48/20 | Harmful: danger of serious damage to health by prolonged exposure through inhalation |

S-phrases

- | | |
|-------|------------------------------------------------------------------------------------------------------------|
| 02 | Keep out of the reach of children |
| 16 | Keep away from sources of ignition - No smoking |
| 23 | Do not breathe spray |
| 36/37 | Wear suitable protective clothing and gloves |
| 45 | In case of accident or if you feel unwell, seek medical advice immediately (show the label where possible) |
| 51 | Use only in well-ventilated areas |
| (63) | (In case of accident by inhalation: remove casualty to fresh air and keep at rest) |

Additional recommendations

- Pressurized container. Protect from sunlight and do not expose to temperatures exceeding 50°C.
- Do not pierce or burn, even after use.
- Do not spray on a naked flame or any incandescent material.
- Contains isocyanates. See information supplied by the manufacturer.
- Persons already sensitised to diisocyanates may develop allergic reactions when using this product.
 - Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product.
 - This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.

2.3 Other hazards:

CLP

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

2 / 14

Soudal Flexifoam

May be ignited by sparks
Gas/vapour spreads at floor level: ignition hazard
Aerosol may explode under the effect of heat

DSD/DPD

May be ignited by sparks
Gas/vapour spreads at floor level: ignition hazard
Aerosol may explode under the effect of heat

SECTION 3: Composition/information on ingredients

3.1 Substances:

Not applicable

3.2 Mixtures:

Name REACH Registration No	CAS No EC No	Conc. (C)	Classification according to DSD/DPD	Classification according to CLP	Note	Remark
tris(2-chloro-1-methylethyl) phosphate 01-2119447716-31	13674-84-5 237-158-7	1%<C<25 %	Xn; R22	Acute Tox. 4; H302	(1)(10)	Constituent
polymethylene polyphenyl isocyanate	9016-87-9	C>25 %	Carc. Cat. 3; R40 Xn; R20 - 48/20 Xi; R36/37/38 R42/43	Carc. 2; H351 Acute Tox. 4; H332 STOT RE 2; H373 Eye Irrit. 2; H319 STOT SE 3; H335 Skin Irrit. 2; H315 Resp. Sens. 1; H334 Skin Sens. 1; H317	(1)(2)(10)	Polymer
propane 01-2119486944-21	74-98-6 200-827-9	1%<C<10 %	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
isobutane 01-2119485395-27	75-28-5 200-857-2	1%<C<10 %	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
dimethyl ether 01-2119472128-37	115-10-6 204-065-8	1%<C<10 %	F+; R12	Flam. Gas 1; H220 Press. Gas - Liquefied gas; H280	(1)(2)(10)	Propellant
(1,3-butadiene, conc<0.1%)						

(1) For R-phrases and H-statements in full: see heading 16

(2) Substance with a Community workplace exposure limit

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

SECTION 4: First aid measures

4.1 Description of first aid measures:

General:

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

After inhalation:

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

After skin contact:

Wash immediately with lots of water. Take victim to a doctor if irritation persists.

After eye contact:

Rinse immediately with plenty of water. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

After ingestion:

Rinse mouth with water. Immediately after ingestion: give lots of water to drink. Do not induce vomiting. Consult a doctor/medical service if you feel

4.2 Most important symptoms and effects, both acute and delayed:

4.2.1 Acute symptoms

After inhalation:

Dry/sore throat. Coughing. Irritation of the respiratory tract. Irritation of the nasal mucous membranes. Runny nose. FOLLOWING SYMPTOMS MAY APPEAR LATER: Possible inflammation of the respiratory tract. Risk of lung oedema. Respiratory difficulties.

After skin contact:

Tingling/irritation of the skin.

After eye contact:

Irritation of the eye tissue. Lacrimation.

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

3 / 14

Soudal Flexifoam

After ingestion:

No effects known.

4.2.2 Delayed symptoms

No effects known.

4.3 Indication of any immediate medical attention and special treatment needed:

If applicable and available it will be listed below.

SECTION 5: Firefighting measures

5.1 Extinguishing media:

5.1.1 Suitable extinguishing media:

Quantities of water. Polyvalent foam. BC powder. Carbon dioxide.

5.1.2 Unsuitable extinguishing media:

No unsuitable extinguishing media known.

5.2 Special hazards arising from the substance or mixture:

On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide). May polymerize on exposure to temperature rise. On heating: release of toxic/combustible gases/vapours (hydrogen cyanide).

5.3 Advice for firefighters:

5.3.1 Instructions:

If exposed to fire cool the closed containers by spraying with water. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion. Dilute toxic gases with water spray. Take account of toxic/corrosive precipitation water.

5.3.2 Special protective equipment for fire-fighters:

Gloves. Protective goggles. Head/neck protection. Protective clothing. Heat/fire exposure: compressed air/oxygen apparatus.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment.

6.1.1 Protective equipment for non-emergency personnel

See heading 8.2

6.1.2 Protective equipment for emergency responders

Gloves. Protective goggles. Head/neck protection. Protective clothing.

Suitable protective clothing

See heading 8.2

6.2 Environmental precautions:

Dam up the solid spill. Use appropriate containment to avoid environmental contamination.

6.3 Methods and material for containment and cleaning up:

Allow product to solidify and remove it by mechanical means. Carefully collect the spill/leftovers. Clean (treat) contaminated surfaces with acetone. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

6.4 Reference to other sections:

See heading 13.

SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

7.1 Precautions for safe handling:

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe very strict hygiene - avoid contact. Remove contaminated clothing immediately.

7.2 Conditions for safe storage, including any incompatibilities:

7.2.1 Safe storage requirements:

Storage temperature: < 50 °C. Store in a cool area. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Unauthorized persons are not admitted. Meet the legal requirements. Max. storage time: 1 year(s).

7.2.2 Keep away from:

Heat sources, ignition sources, (strong) acids, (strong) bases, amines.

7.2.3 Suitable packaging material:

Aerosol.

7.2.4 Non suitable packaging material:

No data available

7.3 Specific end use(s):

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

4 / 14

Soudal Flexifoam

SECTION 8: Exposure controls/personal protection

8.1 Control parameters:

8.1.1 Occupational exposure

a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

The Netherlands

Dimethylether	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	496 ppm
	Time-weighted average exposure limit 8 h (Public occupational exposure limit value)	950 mg/m ³
	Short time value (Public occupational exposure limit value)	783 ppm
	Short time value (Public occupational exposure limit value)	1500 mg/m ³

EU

Dimethylether	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1000 ppm
	Time-weighted average exposure limit 8 h (Indicative occupational exposure limit value)	1920 mg/m ³

Belgium

Hydrocarbures aliphatiques sous forme gazeuse : (Alcanes C1-C4)	Time-weighted average exposure limit 8 h	1000 ppm
Oxyde de diméthyle	Time-weighted average exposure limit 8 h	1000 ppm
	Time-weighted average exposure limit 8 h	1920 mg/m ³

USA (TLV-ACGIH)

Butane, all isomers	Time-weighted average exposure limit 8 h (TLV - Adopted Value)	1000 ppm
---------------------	----------------------------------------------------------------	----------

Germany

Dimethylether	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1900 mg/m ³
Isobutan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	2400 mg/m ³
pMDI (als MDI berechnet)	Time-weighted average exposure limit 8 h (TRGS 900)	0.05 mg/m ³
Propan	Time-weighted average exposure limit 8 h (TRGS 900)	1000 ppm
	Time-weighted average exposure limit 8 h (TRGS 900)	1800 mg/m ³

France

Oxyde de diméthyle	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1000 ppm
	Time-weighted average exposure limit 8 h (VRI: Valeur réglementaire indicative)	1920 mg/m ³

UK

Dimethyl ether	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	400 ppm
	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	766 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	500 ppm
	Short time value (Workplace exposure limit (EH40/2005))	958 mg/m ³
Isocyanates, all (as -NCO) Except methyl isocyanate	Time-weighted average exposure limit 8 h (Workplace exposure limit (EH40/2005))	0.02 mg/m ³
	Short time value (Workplace exposure limit (EH40/2005))	0.07 mg/m ³

b) National biological limit values

If limit values are applicable and available these will be listed below.

8.1.2 Sampling methods

If applicable and available it will be listed below.

Isocyanates	NIOSH	5521
Isocyanates	NIOSH	5522

8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

8.1.4 DNEL/PNEC values

DNEL - Workers

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

5 / 14

Soudal Flexifoam

tris(2-chloro-1-methylethyl) phosphate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute systemic effects dermal	0.528 mg/kg bw/day	
	Acute systemic effects inhalation	0.93 mg/m ³	
	Long-term systemic effects dermal	0.528 mg/kg bw/day	
	Long-term systemic effects inhalation	0.93 mg/m ³	

DNEL - General population

tris(2-chloro-1-methylethyl) phosphate

Effect level (DNEL/DMEL)	Type	Value	Remark
DNEL	Acute systemic effects dermal	0.264 mg/kg bw/day	
	Acute systemic effects inhalation	0.23 mg/m ³	
	Acute systemic effects oral	0.33 mg/kg bw/day	
	Long-term systemic effects dermal	0.264 mg/kg bw/day	
	Long-term systemic effects inhalation	0.23 mg/m ³	
	Long-term systemic effects oral	0.33 mg/kg bw/day	

8.1.5 Control banding

If applicable and available it will be listed below.

8.2 Exposure controls:

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Measure the concentration in the air regularly. Carry operations in the open/under local exhaust/ventilation or with respiratory protection.

8.2.2 Individual protection measures, such as personal protective equipment

Observe very strict hygiene - avoid contact. Do not eat, drink or smoke during work.

a) Respiratory protection:

Wear gas mask with filter type A if conc. in air > exposure limit.

b) Hand protection:

Gloves.

Materials	Breakthrough time	Thickness
LDPE (Low Density Poly Ethylene)	10 minutes	0.025 mm

- materials (good resistance)

LDPE (Low Density Poly Ethylene).

c) Eye protection:

Protective goggles.

d) Skin protection:

Head/neck protection. Protective clothing.

8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties:

Physical form	Aerosol
Odour	Characteristic odour
Odour threshold	No data available
Colour	Variable in colour, depending on the composition
Particle size	No data available
Explosion limits	No data available
Flammability	Extremely flammable aerosol.
Log Kow	Not applicable (mixture)
Dynamic viscosity	No data available
Kinematic viscosity	No data available
Melting point	No data available
Boiling point	No data available
Flash point	No data available
Evaporation rate	No data available
Relative vapour density	> 1
Vapour pressure	No data available
Solubility	water ; insoluble organic solvents ; soluble
Relative density	0.9 ; 20 °C
Decomposition temperature	No data available
Auto-ignition temperature	No data available
Explosive properties	No chemical group associated with explosive properties
Oxidising properties	No chemical group associated with oxidising properties
pH	No data available

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

6 / 14

Soudal Flexifoam

9.2 Other information:

Surface tension	No data available
Absolute density	900 kg/m ³ ; 20 °C

SECTION 10: Stability and reactivity

10.1 Reactivity:

May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard. No data available.

10.2 Chemical stability:

Stable under normal conditions.

10.3 Possibility of hazardous reactions:

May polymerize with many compounds e.g.: (strong) bases and amines. Reacts violently with (some) acids/bases.

10.4 Conditions to avoid:

Use spark-/explosionproof appliances and lighting system. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

10.5 Incompatible materials:

(strong) acids, (strong) bases, amines.

10.6 Hazardous decomposition products:

On heating: release of toxic/combustible gases/vapours (hydrogen cyanide). On burning: release of toxic and corrosive gases/vapours (phosphorus oxides, nitrous vapours, hydrogen chloride, carbon monoxide - carbon dioxide).

SECTION 11: Toxicological information

11.1 Information on toxicological effects:

11.1.1 Test results

Acute toxicity

Soudal Flexifoam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50	Equivalent to OECD 401	1011-1824 mg/kg bw		Rat (male/female)	Experimental value	
Dermal	LD50	OECD 402	> 2000 mg/kg bw	24 h	Rabbit (male/female)	Experimental value	
Inhalation (aerosol)	LC50	Equivalent to OECD 403	> 5 mg/l air	4 h	Rat (male/female)	Weight of evidence	

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Remark
Oral	LD50		> 10000 mg/kg		Rat	Literature study	
Dermal	LD50		> 5000 mg/kg		Rabbit	Literature study	
Inhalation (vapours)	LD50		10-20 mg/l	4 h	Rat	Literature study	

Classification is based on the relevant ingredients

Conclusion

No acute hazard by the inhalation route

Low acute toxicity by the dermal route

Low acute toxicity by the oral route

Corrosion/irritation

Soudal Flexifoam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Not irritating	Equivalent to OECD 405	72 h	24; 48; 72 hours	Rabbit	Experimental value	
Skin	Not irritating	OECD 404	4 h		Rabbit	Experimental value	

polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Time point	Species	Value determination	Remark
Eye	Irritating					Literature study	
Skin	Irritating					Literature study	
Inhalation	Irritating					Literature study	

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

7 / 14

Soudal Flexifoam

Classification is based on the relevant ingredients

Conclusion

Causes skin irritation.
Causes serious eye irritation.
May cause respiratory irritation.
Specific target organ toxicity, single exposure: classified as irritant to respiratory organs

Respiratory or skin sensitisation

Soudal Flexifoam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Not sensitizing	OECD 429			Mouse	Experimental value	

polymethylene polyphenyl isocyanate

Route of exposure	Result	Method	Exposure time	Observation time point	Species	Value determination	Remark
Skin	Sensitizing					Literature study	
Inhalation	Sensitizing					Literature study	

Classification is based on the relevant ingredients

Conclusion

May cause an allergic skin reaction.
May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Specific target organ toxicity

Soudal Flexifoam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Oral	LOAEL	Equivalent to OECD 408	800 ppm	Liver	Weight gain	13 weeks (daily)	Rat (male)	Experimental value
Oral	NOAEL	Equivalent to OECD 408	2500 ppm		No effect	13 weeks (daily)	Rat (female)	Experimental value

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Organ	Effect	Exposure time	Species	Value determination
Inhalation			STOT RE cat.2					Literature study

Classification is based on the relevant ingredients

Conclusion

May cause damage to organs through prolonged or repeated exposure if inhaled.
Low sub-chronic toxicity by the oral route

Mutagenicity (in vitro)

Soudal Flexifoam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Result	Method	Test substrate	Effect	Value determination
Negative		Chinese hamster lung fibroblasts	No effect	Weight of evidence
Negative	Equivalent to OECD 471	Bacteria (S.typhimurium)	No effect	Weight of evidence
Negative	Equivalent to OECD 476	Mouse (lymphoma L5178Y cells)	No effect	Weight of evidence

Mutagenicity (in vivo)

Soudal Flexifoam

No (test)data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

Result	Method	Exposure time	Test substrate	Organ	Value determination
Negative	Equivalent to OECD 475		Rat (male)		Weight of evidence

Carcinogenicity

Soudal Flexifoam

No (test)data on the mixture available

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

8 / 14

Soudal Flexifoam

polymethylene polyphenyl isocyanate

Route of exposure	Parameter	Method	Value	Exposure time	Species	Value determination	Organ	Effect
Inhalation (aerosol)			category 2		Rat	Literature study		Neoplastic effects

Reproductive toxicity

Soudal Flexifoam

No (test) data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

	Parameter	Method	Value	Exposure time	Species	Effect	Organ	Value determination
Developmental toxicity	LOAEL (P)	OECD 416	99 mg/kg bw	>10 weeks (daily)	Rat (female)	Body weight, organ weight, food consumption	Female reproductive organ	Experimental value
	NOAEL (P)	OECD 416	85 mg/kg bw	>10 weeks (daily)	Rat (male)	No effect		Experimental value
	NOAEL	Equivalent to OECD 414	1000 mg/kg bw	70 day(s)	Rat (female)	No effect		Experimental value

Classification is based on the relevant ingredients

Conclusion CMR

Not classified for reprotoxic or developmental toxicity

Not classified for mutagenic or genotoxic toxicity

Suspected of causing cancer.

Chronic effects from short and long-term exposure

Soudal Flexifoam

ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Feeling of weakness. Itching. Skin rash/inflammation. May stain the skin. Dry skin. Coughing. Possible inflammation of the respiratory tract. Respiratory difficulties.

SECTION 12: Ecological information

12.1 Toxicity:

Soudal Flexifoam

No (test) data on the mixture available

tris(2-chloro-1-methylethyl) phosphate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity fishes	LC50		56.2 mg/l	96 h	Brachydanio rerio	Static system	Fresh water	Experimental value; GLP
Acute toxicity invertebrates	EC50	OECD 202	65 - 335 mg/l	48 h	Daphnia magna			Experimental value; GLP
Toxicity algae and other aquatic plants	EC50	OECD 201	73 mg/l	96 h	Selenastrum capricornutum			Experimental value; Growth rate

polymethylene polyphenyl isocyanate

	Parameter	Method	Value	Duration	Species	Test design	Fresh/salt water	Value determination
Acute toxicity other aquatic organisms	LC50		>1000 mg/l	96 h				Literature study
Toxicity aquatic micro-organisms	EC50	OECD 209	>100 mg/l		Activated sludge			Literature study

Classification of the mixture is based on the relevant ingredients of the mixture

Conclusion

Not classified as dangerous for the environment according to the criteria of Directive 1999/45/EC

Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

12.2 Persistence and degradability:

tris(2-chloro-1-methylethyl) phosphate

Biodegradation water

Method	Value	Duration	Value determination
OECD 301E: Modified OECD Screening Test	14 %	28 day(s)	Experimental value
OECD 301C: Modified MITI Test (I)	0 %	28 day(s)	Experimental value

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

9 / 14

Soudal Flexifoam

polymethylene polyphenyl isocyanate

Biodegradation water

Method	Value	Duration	Value determination
OECD 302C: Inherent Biodegradability: Modified MITI Test (II)	< 60 %		Experimental value

Conclusion

Contains non readily biodegradable component(s)

12.3 Bioaccumulative potential:

Soudal Flexifoam

Log Kow

Method	Remark	Value	Temperature	Value determination
	Not applicable (mixture)			

tris(2-chloro-1-methylethyl) phosphate

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		0.8 - 4.6		Cyprinus carpio	Experimental value

Log Kow

Method	Remark	Value	Temperature	Value determination
		2.59		Experimental value

polymethylene polyphenyl isocyanate

BCF fishes

Parameter	Method	Value	Duration	Species	Value determination
BCF		1		Pisces	Literature study

Log Kow

Method	Remark	Value	Temperature	Value determination
	No data available			

Conclusion

Does not contain bioaccumulative component(s)

12.4 Mobility in soil:

No (test)data on mobility of the components available

12.5 Results of PBT and vPvB assessment:

Does not contain component(s) that meet(s) the criteria of PBT and/or vPvB as listed in Annex XIII of Regulation (EC) No 1907/2006.

12.6 Other adverse effects:

Soudal Flexifoam

Global warming potential (GWP)

None of the known components is included in the list of fluorinated greenhouse gases (Regulation (EC) No 842/2006)

Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

tris(2-chloro-1-methylethyl) phosphate

Global warming potential (GWP)

Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 842/2006)

polymethylene polyphenyl isocyanate

Global warming potential (GWP)

Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 842/2006)

SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

13.1 Waste treatment methods:

13.1.1 Provisions relating to waste

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

08 05 01* (wastes not otherwise specified in 08: waste isocyanates).

16 05 04* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing dangerous substances).

Depending on branch of industry and production process, also other waste codes may be applicable. Hazardous waste according to Directive 2008/98/EC.

13.1.2 Disposal methods

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

10 / 14

Soudal Flexifoam

Recycle/reuse. Specific treatment. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals. Do not discharge into drains or the environment.

13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10* (packaging containing residues of or contaminated by dangerous substances).

SECTION 14: Transport information

Road (ADR)

14.1 UN number:

UN number	1950
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Aerosols
----------------------	----------

14.3 Transport hazard class(es):

Hazard identification number	
Class	2
Classification code	5F

14.4 Packing group:

Packing group	
Labels	2.1

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
------------------------------------------	----

14.6 Special precautions for user:

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Rail (RID)

14.1 UN number:

UN number	1950
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Aerosols
----------------------	----------

14.3 Transport hazard class(es):

Hazard identification number	23
Class	2
Classification code	5F

14.4 Packing group:

Packing group	
Labels	2.1

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
------------------------------------------	----

14.6 Special precautions for user:

Special provisions	190
Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Inland waterways (ADN)

14.1 UN number:

UN number	1950
-----------	------

14.2 UN proper shipping name:

Proper shipping name	Aerosols
----------------------	----------

14.3 Transport hazard class(es):

Class	2
Classification code	5F

14.4 Packing group:

Packing group	
Labels	2.1

14.5 Environmental hazards:

Environmentally hazardous substance mark	no
------------------------------------------	----

14.6 Special precautions for user:

Special provisions	190
--------------------	-----

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

11 / 14

Soudal Flexifoam

Special provisions	327
Special provisions	344
Special provisions	625
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)

Sea (IMDG/IMSBC)

14.1 UN number:	
UN number	1950
14.2 UN proper shipping name:	
Proper shipping name	Aerosols
14.3 Transport hazard class(es):	
Class	2.1
14.4 Packing group:	
Packing group	
Labels	2.1
14.5 Environmental hazards:	
Marine pollutant	-
Environmentally hazardous substance mark	no
14.6 Special precautions for user:	
Special provisions	63
Special provisions	190
Special provisions	277
Special provisions	327
Special provisions	344
Special provisions	959
Limited quantities	Combination packagings: not more than 1 liter per inner packaging for liquids. A package shall not weigh more than 30 kg. (gross mass)
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code:	
Annex II of MARPOL 73/78	Not applicable

Air (ICAO-TI/IATA-DGR)

14.1 UN number:	
UN number	1950
14.2 UN proper shipping name:	
Proper shipping name	Aerosols, flammable
14.3 Transport hazard class(es):	
Class	2.1
14.4 Packing group:	
Packing group	
Labels	2.1
14.5 Environmental hazards:	
Environmentally hazardous substance mark	no
14.6 Special precautions for user:	
Special provisions	A145
Special provisions	A167
Special provisions	A802
Passenger and cargo transport: limited quantities: maximum net quantity per packaging	30 kg G

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

European legislation:

VOC content Directive 2010/75/EU

VOC content	Remark
17 %	

REACH Annex XVII - Restriction

Contains component(s) subject to restrictions of Annex XVII of Regulation (EC) No 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

	Designation of the substance, of the group of substances or of the mixture	Conditions of restriction
tris(2-chloro-1-methylethyl) phosphate polymethylene polyphenyl isocyanate	Liquid substances or mixtures which are regarded as dangerous in accordance with Directive 1999/45/EC or are fulfilling the criteria for any of the following hazard classes or categories set out in Annex I to Regulation (EC) No 1272/2008: (a) hazard classes 2.1 to 2.4, 2.6 and 2.7, 2.8	1. Shall not be used in: — ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays, — tricks and jokes, — games for one or more participants, or any article intended to be used as such, even with ornamental aspects. 2. Articles not complying with paragraph 1 shall not be placed on the market. 3. Shall not be placed on the market if they contain a colouring agent,

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

12 / 14

Soudal Flexifoam

	types A and B, 2.9, 2.10, 2.12, 2.13 categories 1 and 2, 2.14 categories 1 and 2, 2.15 types A to F; (b) hazard classes 3.1 to 3.6, 3.7 adverse effects on sexual function and fertility or on development, 3.8 effects other than narcotic effects, 3.9 and 3.10; (c) hazard class 4.1; (d) hazard class 5.1.	unless required for fiscal reasons, or perfume, or both, if they: — can be used as fuel in decorative oil lamps for supply to the general public, and, — present an aspiration hazard and are labelled with R65 or H304.4. Decorative oil lamps for supply to the general public shall not be placed on the market unless they conform to the European Standard on Decorative oil lamps (EN 14059) adopted by the European Committee for Standardisation (CEN).5. Without prejudice to the implementation of other Community provisions relating to the classification, packaging and labelling of dangerous substances and mixtures, suppliers shall ensure, before the placing on the market, that the following requirements are met: a) lamp oils, labelled with R65 or H304, intended for supply to the general public are visibly, legibly and indelibly marked as follows: "Keep lamps filled with this liquid out of the reach of children"; and, by 1 December 2010, "Just a sip of lamp oil — or even sucking the wick of lamps — may lead to life-threatening lung damage"; b) grill lighter fluids, labelled with R65 or H304, intended for supply to the general public are legibly and indelibly marked by 1 December 2010 as follows: "Just a sip of grill lighter may lead to life threatening lung damage"; c) lamp oils and grill lighters, labelled with R65 or H304, intended for supply to the general public are packaged in black opaque containers not exceeding 1 litre by 1 December 2010.6. No later than 1 June 2014, the Commission shall request the European Chemicals Agency to prepare a dossier, in accordance with Article 69 of the present Regulation with a view to ban, if appropriate, grill lighter fluids and fuel for decorative lamps, labelled R65 or H304, intended for supply to the general public.7. Natural or legal persons placing on the market for the first time lamp oils and grill lighter fluids, labelled with R65 or H304, shall by 1 December 2011, and annually thereafter, provide data on alternatives to lamp oils and grill lighter fluids labelled R65 or H304 to the competent authority in the Member State concerned. Member States shall make those data available to the Commission.'
polymethylene polyphenyl isocyanate	Methylenediphenyl diisocyanate (MDI) including the following specific isomers: 4,4'-Methylenediphenyl diisocyanate; 2,4'-Methylenediphenyl diisocyanate; 2,2'-Methylenediphenyl diisocyanate	1. Shall not be placed on the market after 27 December 2010, as a constituent of mixtures in concentrations equal to or greater than 0,1 % by weight of MDI for supply to the general public, unless suppliers shall ensure before the placing on the market that the packaging: (a) contains protective gloves which comply with the requirements of Council Directive 89/686/EEC; (b) is marked visibly, legibly and indelibly as follows, and without prejudice to other Community legislation concerning the classification, packaging and labelling of substances and mixtures: " — Persons already sensitised to diisocyanates may develop allergic reactions when using this product. — Persons suffering from asthma, eczema or skin problems should avoid contact, including dermal contact, with this product. — This product should not be used under conditions of poor ventilation unless a protective mask with an appropriate gas filter (i.e. type A1 according to standard EN 14387) is used.2. By way of derogation, paragraph 1(a) shall not apply to hot melt adhesives.

National legislation The Netherlands

Soudal Flexifoam

Waste identification (the Netherlands)	LWCA (the Netherlands): KGA category 06
Waterbezwaarlijkheid	8

National legislation Germany

Soudal Flexifoam

WGK	1: Classification water polluting based on the components in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 4)
-----	-----------------------------------------------------------------------------------------------------------------------------------------------------------------

polymethylene polyphenyl isocyanate

TRGS905 - Krebserzeugend	3
TRGS905 - Erbgutverändernd	-
TRGS905 - Fruchtbarkeitsgefährdend	-
TRGS905 - Fruchtschädigend	-
MAK - Krebserzeugend Kategorie	4
Schwangerschaft Gruppe	C
MAK 8-Stunden-Mittelwert mg/m ³	„polymeres MDI“ (einatembare Fraktion); 0.05 mg/m ³ ; gemessen als einatembare Fraktion (vgl. Abschn. Vd) S. 191)

National legislation France

Soudal Flexifoam

No data available

National legislation Belgium

Soudal Flexifoam

No data available

Other relevant data

Soudal Flexifoam

No data available

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Soudal Flexifoam

polymethylene polyphenyl isocyanate

IARC - classification

3; Polymethylene polyphenyl isocyanate

15.2 Chemical safety assessment:

No chemical safety assessment is required.

SECTION 16: Other information

Full text of any R-phrases referred to under headings 2 and 3:

R20 Harmful by inhalation
R22 Harmful if swallowed
R36/37/38 Irritating to eyes, respiratory system and skin
R40 Limited evidence of a carcinogenic effect
R42/43 May cause sensitisation by inhalation and skin contact
R48/20 Harmful: danger of serious damage to health by prolonged exposure through inhalation

Full text of any H-statements referred to under headings 2 and 3:

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H229 Pressurised container: May burst if heated.
H280 Contains gas under pressure; may explode if heated.
H302 Harmful if swallowed.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H332 Harmful if inhaled.
H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335 May cause respiratory irritation.
H351 Suspected of causing cancer.
H373 May cause damage to organs through prolonged or repeated exposure if inhaled.

(*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

DSD Dangerous Substance Directive

DPD Dangerous Preparation Directive

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Reason for revision: 2.2

Publication date: 2005-07-07

Date of revision: 2014-12-19

Revision number: 0702

Product number: 42359

14 / 14